

# **FLEX-TECH** POTABLE WATER HOSE

HOSE & TUBING, LLC.

**NSF/ANSI-61 Certified Hose for drinking water system components.**

**POTENTIAL USE:**

- Domestic hot and cold water applications
- Drinking water applications

**FEATURES:**

- Constructed of PVC materials sanctioned for food contact use under CFR title 21, parts 170-199
- Material compounds contain no substances designated as hazardous under California Proposition 65
- Non-marking
- Lightweight
- When coupled properly, 1/4" – 1/2" sizes will conform to high-temp extreme test requirements as defined by ASME A112.18.6, Section 4.3
- Can be ordered with or without tracer yarn - when ordering with tracer yarn for color-coding please specify red or blue



**CONSTRUCTION:**

- **Tube:** White PVC compound specially formulated in compliance with applicable FDA regulations, NSF/ANSI standard 61, and California Proposition 65
- **Reinforcement:** High Tensile Strength Textile Cord
- **Cover:** Clear PVC compound specially formulated in compliance with applicable FDA regulations, NSF/ANSI standard 61, and California Proposition 65

**TEMPERATURE:** 14° F (4° C) to 140° F (65° C) continuous service – All sizes

**PACKAGING:** Coiled, tied, and individually bagged in heavy-duty, clear plastic bags.

Part#	I.D.	O.D.	Max W.P.	Wt./ ft	Lengths
PW-0250CW <b>X</b> -00	1/4"	0.475	300 psi	0.069	500/100 ft
PW-0313CW <b>X</b> -00	5/16"	0.531	300 psi	0.080	500/100 ft
PW-0375CW <b>X</b> -00	3/8"	0.595	300 psi	0.098	500/100 ft
PW-0500CW <b>X</b> -00	1/2"	0.750	300 psi	0.140	300/100 ft
PW-0625CW <b>X</b> -00	5/8"	0.895	200 psi	0.180	200/100 ft
PW-0750CW <b>X</b> -00	3/4"	1.045	150 psi	0.215	200/100 ft
PW-1000CW <b>X</b> -00	1"	1.315	150 psi	0.315	200/100 ft

\* When ordering with tracer, substitute **X** for R = Red or B = Blue. If no tracer, leave out **X**